

DELUXE SERIES

Housing Dimensions

- 9-1/8" L x 9-1/8" W x 7-5/8" H

Housing

- Heavy-duty steel housing coated with rust proof paint
- Adjustable double bar hanger system that extends up to 24"
- 4" exhaust pipe connection
- Wired for both fan or fanlight
- Effortless side electrical connection
- Termination damper to prevent cold air infiltration
- Light, durable, and sturdy

Motor and Blower

- Power rating of 120V/60Hz
- Permanently lubricated, energy efficient motor with **ball bearings** designed for continuous use
- Quick installation of motor and impeller assembly
- Effortless snap in wiring connection
- UL and cUL listed for tub/shower enclosure when connected to a GFCI protected branch circuit

Grille

- Contemporary design - with or without light kit
- Durable white ABS for easy cleaning
- Torsion spring clips included for easy mounting
- Electronic ballast

Warranty

- 2 year limited warranty

Lighting

FANLIGHTS

Included:
2 - 18 Watt Flicker-Free,
Electronic Ballast
Compact Fluorescent Lamps



FANLIGHT MODEL

See Fan Curve (4) on Pg.16 or
See Fan Curve (5) on Pg.17



TITLE 24
COMPLIANT

FANS						FANLIGHTS			
Cat. No.		OD80*	OD90*	OD110*	OD120*	OD80L	OD90L	OD110L	OD120L
Static pressure	Inches w.g.	0.1"	0.1"	0.1"	0.1"	0.1"	0.1"	0.1"	0.1"
Air volume	CFM	80	90	110	120	80	90	110	120
Noise	Sone	0.8	1.0	1.5	2.0	0.5	0.7	1.2	1.5
Power consumption	Watts	27.9	28.4	30.6	32.1	31.6	32.1	33.7	37.0
Energy efficiency	CFM/Watts	2.87	3.17	3.59	3.74	2.53	2.80	3.26	3.24
Speed	RPM	946	965	1,083	1,153	990	1,017	1,126	1,201
Current	Amps	.18	.18	.19	.2	.27	.26	.27	.30
Power rating	V/Hz.	120/60	120/60	120/60	120/60	120/60	120/60	120/60	120/60
Duct diameter	Inches	4"	4"	4"	4"	4"	4"	4"	4"
Motor type		Enclosed	Enclosed	Enclosed	Enclosed	Enclosed	Enclosed	Enclosed	Enclosed
Weight	lbs	10	10	10	10	10	10	10	10
Master Qty.		4	4	4	4	4	4	4	4