



**SKU:** R-16

**UPC:** 0783669769333

**Features & Benefits:**

**Description:** Phenolic Black Mounting Block for Neutral Bars

## Specs

### Additional Class Attributes

Connection	Mechanical
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	2
Number of Poles	1
Number of Ports Tap	0
Replacement Part(s)	E-153
Type of Accessory	E-223

### Dimensions

Dimension G (IN)	0.375
Dimension G (mm)	9.525
Drive Size Main	NA
Height (IN)	1
Height BX (IN)	2
Height (mm)	25.4
Length (IN)	2.5
Length (mm)	63.5
Mounting Bolt/Stud Size (mm)	254
Mounting Hole Diameter (IN)	0.282
Mounting Hole Spacing (IN)	1.693
Mounting Hole Spacing (mm)	43.0022
Weight (LB)	0.119
Weight BX (LB)	2.03
Width (IN)	2.5
Width BX (IN)	6.1875
Width (mm)	63.5

### Material and Finish

Connector Finish	NA
Insulation	NA
Material	Phenolic

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10
-------------------------	-----

Number of Wire Binding Screws per Port	NA
Wire Binding Screw Size	NA

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
NEMA Code	S-588-3
UPC Code	78366976933

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
UL Control Number	NA
UL File Number	NA

### Color

Color	Black
-------	-------

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	NA
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA