

IMAGE  
COMING  
SOON

**SKU:** T244/21C12

**UPC:** 0783669920062

**Features & Benefits:**

**Description:** Copper Flex Braid Connector, 2 Braids, 12in, 1 Hole, 1/2in Bolt Size, Tin Plated

## Specs

### Additional Class Attributes

Circular Mils/Braid	48000
Mounting Hole Type	Thru
Shape Of Conductor	Flat

### Dimensions

Height (IN)	0
Height BX (IN)	2
Length (IN)	12
Length (mm)	304.8
Thickness (IN)	0.125
Thickness (mm)	3.175
Weight (LB)	1.015
Weight BX (LB)	1.162
Width (IN)	1
Width BX (IN)	6.1875
Width (mm)	25.4

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366992006

### Testing Standards

**Prop65 Compliance**

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

UL Control Number	667P
UL / CULUS Specification	UL/cUL 467 Listed
UL File Number	E34440

### *Environment and Temperature*

Temperature Rating	NA
--------------------	----

### *Additional Technical Specifications*

Connector Amperage Rating AL (Derated where applicable)	NA
Connector Amperage Rating CU (Derated where applicable)	145 Amps
Conductor Type	Braid