

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : General Single-Phase

Product code : 10160235
Catalog # : 00336ES1E145T

Frame	: G143/5T	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 3 HP (2.2 kW)	Temperature rise	: 105 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 14.0-12.0/6.00 A	Protection degree	: IP55
L. R. Amperes	: 119-102/51.0 A	Cooling method	: IC411 - TEFC
LRC	: 8.5x(Code J)	Mounting	: F-1
No load current	: 1.98-2.30/1.15 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3490 rpm	Noise level ²	: 60.0 dB(A)
Slip	: 3.06 %	Starting method	: Direct On Line
Rated torque	: 4.51 ft.lb	Approx. weight ³	: 55.5 lb
Locked rotor torque	: 250 %		
Breakdown torque	: 280 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0949 sq.ft.lb		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	75.3	77.0	82.5	84.0	Max. traction	: 82 lb
Power Factor	0.75	0.96	0.97	0.97	Max. compression	: 138 lb

	Drive end	Non drive end
Bearing type	: 6205 ZZ	: 6203 ZZ
Sealing	: V'Ring	: V'Ring
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	25/03/2024			
			Revision	