

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium Efficiency  
Three-Phase

Product code : 12845391

Catalog # : 00336ET3H182TC-S

Frame : 182/4TC  
Output : 3 HP (2.2 kW)  
Poles : 2  
Frequency : 60 Hz  
Rated voltage : 575 V  
Rated current : 3.01 A  
L. R. Amperes : 26.5 A  
LRC : 8.8x(Code K)  
No load current : 1.36 A  
Rated speed : 3515 rpm  
Slip : 2.36 %  
Rated torque : 4.48 ft.lb  
Locked rotor torque : 240 %  
Breakdown torque : 350 %  
Insulation class : F  
Service factor : 1.15  
Moment of inertia (J) : 0.1564 sq.ft.lb  
Design : B

Locked rotor time : 45s (cold) 25s (hot)  
Temperature rise : 80 K  
Duty cycle : Cont.(S1)  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Protection degree : IP55  
Cooling method : IC411 - TEFC  
Mounting : F-1  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 68.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 71.6 lb

Output	50%	75%	100%
Efficiency (%)	84.0	86.5	86.5
Power Factor	0.70	0.80	0.85

Foundation loads  
Max. traction : 64 lb  
Max. compression : 136 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
14.2	10.4	10.2	8.6	4.8	3.5	2.2

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type :		6206 ZZ	6205 ZZ
Sealing :		V'Ring	Without Bearing Seal
Lubrication interval :		-	-
Lubricant amount :		-	-
Lubricant type :		Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
		Revision		