DATA SHEET

Three Phase Induction Motor - Squirrel Cage



11110011114									
Customer	:								
Product line	: R	olled Steel	Standard	Efficiency Th	nree- Product code :	14797780			
	Ph	ase							
					Catalog # :	.7536ES3V56C-S			
Frame		: 560			Locked rotor time	: 41s (cold) 23s (hot)			
Output			5 HP (0.55	kW)	Temperature rise	: 80 K			
Poles	: 2				Duty cycle	: Cont.(S1)			
Frequency : 60 Hz					Ambient temperature				
Rated voltage : 200/400 V					Altitude	: 1000 m.a.s.l.			
Rated current : 2.60/1.30 A					Protection degree	: IP55			
L. R. Amperes : 18.2/9.10 A					Cooling method	: IC411 - TEFC			
LRC : 7.0x(Code K)					Mounting	: F-1			
No load current : 1.27/0.633 A					Rotation ¹	: Both (CW and CCW)			
Rated speed : 3475 rpm					Noise level ²	: 68.0 dB(A)			
Slip : 3.47 %					Starting method	: Direct On Line			
Rated torque : 1.13 ft.lb Locked rotor torque : 250 %					Approx. weight ³	: 21.8 lb			
Locked rotor tor	: 250								
Breakdown torque : Insulation class :			70						
Service factor :			5						
			5 17 sq.ft.lb						
Wornerit of mert	ia (0)	. 0.00	717 3q.it.ib						
Output	25%	50%	75%	100%	Foundation loads				
Efficiency (%)	58.8	62.0	68.0	72.0	Max. traction	: 21 lb			
Power Factor	0.45	0.70	0.79	0.85	Max. compression	: 43 lb			
			Driv	re end	Non drive end	1			
Bearing type	:	62	203 ZZ	6202 ZZ					
Sealing	:	V	"Ring	Without Bearing Seal					
Lubrication inter	:		-	-					
Lubricant amou	:	-							
Lubricant type	:	Mobil Polyrex EM							

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			1/1	