## **DATA SHEET**



Three Phase Induction Motor - Squirrel Cage Customer Product line : W22 High Efficiency Three-Phase Product code: 11355039 : 36s (cold) 20s (hot) Frame : 444/5T Locked rotor time Output : 75 HP (55 kW) Temperature rise : 80 K Poles Duty cycle : 8 : Cont.(S1) Frequency : 60 Hz Ambient temperature : -20°C to +40°C Rated voltage : 230/460 V Altitude : 1000 m.a.s.l. Rated current : 186/92.8 A Protection degree : IP55 Cooling method : IC411 - TEFC L. R. Amperes : 1039/520 A LRC : 5.6x(Code F) Mounting : F-1 : 72.0/36.0 A No load current Rotation<sup>1</sup> : Both (CW and CCW) Rated speed : 885 rpm Noise level<sup>2</sup> : 63.0 dB(A) Slip : 1.67 % Starting method : Direct On Line Rated torque : 445 ft.lb Approx. weight3 : 1495 lb Locked rotor torque : 170 % Breakdown torque : 200 % Insulation class : F Service factor : 1.25 Moment of inertia (J) : 73.6 sq.ft.lb Design Output 50% 75% 100% Foundation loads Efficiency (%) 93.0 92.0 93.0 92.8 93.0 92.8 Max. traction : 1976 lb 92.0 92.0 92.8 92.8 92.8 92.8 Power Factor 0.67 0.67 0.76 0.77 0.80 0.80 Max. compression : 3472 lb 0.63 0.60 0.74 0.72 0.79 0.77 Losses at normative operating points (speed;torque), in percentage of rated output power P1 (0,9;1,0) 7.4 7.4 7.4 7.1 P2 (0,5;1,0) 5.7 5.9 5.9 5.9 P3 (0,25;1,0) 5.3 5.5 5.5 5.5 Losses (%) P4 (0,9;0,5) 3.3 3.5 3.5 3.5 P5 (0,5;0,5) 2.2 2.3 2.3 2.3 1.5 P6 (0,5;0,25) 1.4 1.5 1.5 P7 (0,25;0,25) 1.0 1.0 1.0 1.0 Drive end Non drive end Bearing type 6319 C3 6316 C3 WSeal Sealing WSeal 17000 h 20000 h Lubrication interval Lubricant amount 45 g 34 g Mobil Polyrex EM Lubricant type Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	29/03/2024			1/1	