

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Standard Efficiency Three-Phase Product code : 12894766

Frame	: 56C	Locked rotor time	: 16s (cold) 9s (hot)
Output	: 1.5 HP (1.1 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 4.46/2.23 A	Protection degree	: IP55
L. R. Amperes	: 33.5/16.7 A	Cooling method	: IC411 - TEFC
LRC	: 7.5x(Code K)	Mounting	: F-1
No load current	: 3.00/1.50 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1750 rpm	Noise level ²	: 52.0 dB(A)
Slip	: 2.78 %	Starting method	: Direct On Line
Rated torque	: 4.50 ft.lb	Approx. weight ³	: 31.8 lb
Locked rotor torque	: 250 %		
Breakdown torque	: 300 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.1037 sq.ft.lb		
Design	: A		

Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	75.4	78.0	77.0	77.4	80.0	79.1	81.5	77.9	Max. traction	: 128 lb
	72.2		73.3		77.4		78.1			
Power Factor	0.30	0.36	0.54	0.62	0.67	0.76	0.76	0.83	Max. compression	: 160 lb
	0.28		0.52		0.67		0.77			

					<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:				6204 ZZ	6202 ZZ
Sealing	:				V'Ring	Without Bearing Seal
Lubrication interval	:				-	-
Lubricant amount	:				-	-
Lubricant type	:				Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	27/03/2024			
			Page	Revision
			1 / 1	