

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Standard Efficiency Three-Phase  
Product code : 12894765

Frame	: 56C	Locked rotor time	: 14s (cold) 8s (hot)
Output	: 2 HP (1.5 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 5.70/2.85 A	Protection degree	: IP55
L. R. Amperes	: 41.6/20.8 A	Cooling method	: IC411 - TEFC
LRC	: 7.3x(Code K)	Mounting	: F-1
No load current	: 3.33/1.66 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 1745 rpm	Noise level <sup>2</sup>	: 52.0 dB(A)
Slip	: 3.06 %	Starting method	: Direct On Line
Rated torque	: 6.02 ft.lb	Approx. weight <sup>3</sup>	: 35.2 lb
Locked rotor torque	: 240 %		
Breakdown torque	: 270 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.1232 sq.ft.lb		
Design	: A		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	80.0	81.5	82.5	Max. traction	: 142 lb
Power Factor	0.58	0.72	0.80	Max. compression	: 177 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6204 ZZ	6202 ZZ
Sealing	:	V'Ring	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:  
USABLE @208V 6.30A SF 1.00 SFA 6.30A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
			Revision	