

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 High Efficiency Three-Phase

Product code : 11356430

Frame	: 447/9T	Locked rotor time	: 19s (cold) 11s (hot)
Output	: 250 HP (185 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 291 A	Protection degree	: IP55
L. R. Amperes	: 1804 A	Cooling method	: IC411 - TEFC
LRC	: 6.2x(Code G)	Mounting	: F-1
No load current	: 105 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1185 rpm	Starting method	: Direct On Line
Slip	: 1.25 %	Approx. weight ³	: 2653 lb
Rated torque	: 1110 ft.lb		
Locked rotor torque	: 220 %		
Breakdown torque	: 220 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 153 sq.ft.lb		
Design	: B		

Output	25%		50%		75%		100%		Foundation loads	
Efficiency (%)	95.2	93.4	95.0	93.6	95.4	94.5	95.0	94.5	Max. traction	: 6135 lb
	94.3	94.3	94.5	94.5	95.0	95.0	95.0	95.0		
Power Factor	0.46	0.52	0.71	0.76	0.80	0.83	0.84	0.85	Max. compression	: 8788 lb
	0.48	0.46	0.73	0.71	0.81	0.80	0.85	0.84		

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	5.4	6.0	5.4	5.4
	P2 (0,5;1,0)	4.5	5.0	4.5	4.5
	P3 (0,25;1,0)	4.1	4.6	4.1	4.1
	P4 (0,9;0,5)	2.6	2.9	2.6	2.6
	P5 (0,5;0,5)	1.9	2.1	1.9	1.9
	P6 (0,5;0,25)	1.3	1.4	1.3	1.3
	P7 (0,25;0,25)	0.8	0.9	0.8	0.8

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6322 C3	6319 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	11000 h	13000 h
Lubricant amount	:	60 g	45 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	28/03/2024			
			Revision	