## **DATA SHEET**

Date

## Three Phase Induction Motor - Squirrel Cage



Customer Product line : W22 NEMA Premium Efficiency Three-Product code: 11457101 Catalog #: 00112ET3H145T-W22 Frame : 143/5T Locked rotor time : 50s (cold) 28s (hot) Output : 1 HP (0.75 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) : -20°C to +40°C Frequency : 60 Hz Ambient temperature Rated voltage : 1000 m.a.s.l. : 575 V Altitude Rated current : 1.38 A Protection degree : IP55 L. R. Amperes : 8.58 A Cooling method : IC411 - TEFC LRC : 6.2x(Code K) Mounting : F-1 No load current : 0.880 A Rotation<sup>1</sup> : Both (CW and CCW) Rated speed : 1160 rpm Noise level<sup>2</sup> : 50.0 dB(A) Starting method Slip : 3.33 % : Direct On Line Rated torque : 4.53 ft.lb Approx. weight3 : 51.5 lb Locked rotor torque : 260 % : 300 % Breakdown torque Insulation class : F Service factor : 1.25 Moment of inertia (J) : 0.1595 sq.ft.lb Design : B 25% 75% 100% Output 50% Foundation loads Efficiency (%) 76.0 77.0 82.0 82.5 Max. traction : 92 lb Power Factor 0.26 0.45 0.57 0.66 Max. compression : 144 lb Losses at normative operating points (speed;torque), in percentage of rated output power P2 (0,5;1,0) P3 (0,25;1,0) P4 (0,9;0,5) P1 (0,9;1,0) P5 (0,5;0,5) P6 (0,5;0,25) P7 (0,25;0,25) 20.0 16.7 16.9 12.6 9.2 7.6 5.8 Drive end Non drive end 6205 ZZ 6204 ZZ Bearing type V'Ring Sealing V'Ring Lubrication interval Lubricant amount Lubricant type Mobil Polyrex EM Notes: This revision replaces and cancel the previous one, which These are average values based on tests with sinusoidal must be eliminated. power supply, subject to the tolerances stipulated in NEMA (1) Looking the motor from the shaft end. MG-1. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load. Rev. **Changes Summary** Performed Checked Date Performed by Checked by Page Revision 26/03/2024 1/1