## DATA SHEET

Date

29/03/2024



Customer	:							
Product line	: W22 NEMA Premium Efficiency Thre Phase				Product code :  Catalog # :		12445972 00718ET3P213T-W22	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor tord Breakdown torqu Insulation class		: 213/5T : 7.5 HP (5.5 kW) : 4 : 60 Hz : 200 V : 21.1 A : 150 A : 7.1x(Code H) : 9.66 A : 1765 rpm : 1.94 % : 22.3 ft.lb : 220 % : 310 % : F			Catalog #:  Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³		: 36s (cold) 20s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 58.0 dB(A) : Direct On Line : 166 lb	
Service factor Moment of inerti Design		: B	4 sq.ft.lb					
Output	25%	50%	75%	100%	Foundation loads			
Efficiency (%) Power Factor	88.6 0.40	89.5 0.66	91.0 0.76	91.7 0.82	Max. trac	ction npression	: 307 lb : 473 lb	
						•		
						ated output power		D7 (0.05,0.05
P1 (0,9;1,0) 8.8		P2 (0,5;1,0) P3 (0,25;1,0) 7.0 6.5			(0,9;0,5) P5 (0,5;0,5) 4.9 3.3		P6 (0,5;0,25)	P7 (0,25;0,25
		630	Drive end         Non drive en           6308 ZZ         6207 ZZ           V'Ring         V'Ring           -         -           -         -           -         -           Mobil Polyrex EM		<u>1</u>			
This revision replants to eliminate	ed.			ne, which	power s	re average values upply, subject to th		
(1) Looking the m (2) Measured at (3) Approximate manufacturing pr (4) At 100% of fu	1m and wit weight sub ocess.	th toleranc ject to cha	e of +3dB(A anges after		MG-1.			
Rev.		Ch	anges Sum	mary		Performed	Checked	Date
Performed by Checked by							Page	Revision

1/1