DATA SHEET

Date

28/03/2024



Customer	:							
Product line	: W22 NEMA Premium Efficiency Thre Phase				ee- Product code :		11573136	
	ГПс	150				Catalog # :	01536ET3F	H254TF2-W22
Poles : 2			HP (11 kW)		Locked rotor time Temperature rise Duty cycle		: 45s (cold) 25s (hot) : 80 K : Cont.(S1)	
Rated voltage : 5 Rated current : 1 L. R. Amperes : 9		: 575 : 13.8	: 60 Hz : 575 V : 13.8 A : 92.2 A		Ambient temperature Altitude Protection degree Cooling method		: -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC	
LRC No load current Rated speed Slip		: 4.24	0 rpm		Mounti Rotatio Noise I	on¹	: F-2 : Both (CW : 72.0 dB(/ : Direct Or	
Rated torque Locked rotor tord Breakdown torqu Insulation class		: 22.3 : 220 : 270 : F	3 ft.lb % %			c. weight ^a	: 249 lb	i Line
Service factor Moment of inerti- Design	a (J)	: 1.25 : 1.26 : B	sq.ft.lb					
Output	25%	50%	75%	100%	Foundation loads			
Efficiency (%) Power Factor	89.2 0.53	89.5 0.77		91.0 0.88	Max. traction Max. compression		: 164 lb : 413 lb	
Losses at normat	tive operat	ing points	(speed;torque	e), in perce	entage of r	ated output power		
P1 (0,9;1,0) 9.4		P2 (0,5;1,0) P3 (6 (0,25;1,0) P4 (0, 6.8 4		P5 (0,5;0,5) 2.8	P6 (0,5;0,25)	P7 (0,25;0,25
Bearing type Sealing Lubrication interval Lubricant amount Lubricant type		: : :	<u>Drive end</u> 6309 C3 V'Ring 19000 h 13 g		Non drive end 6209 C3 V'Ring 20000 h 9 g bil Polyrex EM			
Notes:								
This revision repl must be eliminate (1) Looking the m (2) Measured at a (3) Approximate wanufacturing pro (4) At 100% of fu	ed. notor from 1m and wit weight sub ocess.	the shaft e	nd. e of +3dB(A).			re average values upply, subject to th		
Rev.	ıı ıoau.	Ch	anges Summ	arv		Performed	Checked	Date
Performed by Checked by				,		3.300	Page	Revision

1/1