

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 15139411

Catalog # : 01536ET3EPM254/6Y-W2

Frame	: 256TZ	Locked rotor time	: 45s (cold) 25s (hot)
Output	: 15 HP (11 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 38.1-34.5/17.2 A	Protection degree	: IP55
L. R. Amperes	: 255-231/115 A	Cooling method	: IC418 - TEAO
LRC	: 6.7x(Code G)	Mounting	: F-1
No load current	: 10.3-12.0/6.00 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3530 rpm	Starting method	: Direct On Line
Slip	: 1.94 %	Approx. weight ³	: 595 lb
Rated torque	: 22.3 ft.lb		
Locked rotor torque	: 220 %		
Breakdown torque	: 270 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 1.26 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads				
Efficiency (%)	0.000	89.5	89.5	91.0	90.2	91.0	89.5	Max. traction	: -37 lb
	0.000								
Power Factor	0.00	0.00	0.77	0.83	0.85	0.88	0.88	0.90	Max. compression : 557 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6309 C3	6209 C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	19000 h	20000 h
Lubricant amount	:	13 g	9 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	28/03/2024			
			Revision	