

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : General Standard Efficiency Three-Phase Product code : 11041432

Frame	: D56C	Locked rotor time	: 18s (cold) 10s (hot)
Output	: 2 HP (1.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 2.14 A	Protection degree	: IP21
L. R. Amperes	: 17.4 A	Cooling method	: IC01 - ODP
LRC	: 8.1x(Code K)	Mounting	: F-1
No load current	: 1.03 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3460 rpm	Starting method	: Direct On Line
Slip	: 3.89 %	Approx. weight ³	: 31.0 lb
Rated torque	: 3.04 ft.lb		
Locked rotor torque	: 350 %		
Breakdown torque	: 340 %		
Insulation class	: B		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0413 sq.ft.lb		
Design	: A		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	77.2	78.0	80.5	81.0	Max. traction	: 86 lb
Power Factor	0.41	0.68	0.80	0.87	Max. compression	: 117 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6204 ZZ	6203 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	25/03/2024			
			Revision	