

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12199325

Catalog # : 15012ET3H447T-W22

Frame	: 445/7T	Locked rotor time	: 36s (cold) 20s (hot)
Output	: 150 HP (110 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 141 A	Protection degree	: IP55
L. R. Amperes	: 872 A	Cooling method	: IC411 - TEFC
LRC	: 6.2x(Code G)	Mounting	: F-1
No load current	: 54.4 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 1189 rpm	Noise level <sup>2</sup>	: 69.0 dB(A)
Slip	: 0.92 %	Starting method	: Direct On Line
Rated torque	: 662 ft.lb	Approx. weight <sup>3</sup>	: 2203 lb
Locked rotor torque	: 240 %		
Breakdown torque	: 250 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 134 sq.ft.lb		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	95.0	95.4	95.8	Max. traction	: 3314 lb
Power Factor	0.67	0.78	0.82	Max. compression	: 5516 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
4.6	3.8	3.4	2.4	1.7	1.2	0.7

	Drive end	Non drive end
Bearing type	: 6319 C3	: 6316 C3
Sealing	: WSeal	: WSeal
Lubrication interval	: 13000 h	: 16000 h
Lubricant amount	: 45 g	: 34 g
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			

Page 1 / 1  
Revision