

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12451572

Catalog # : Z07518ET3X122220

Frame : 364/5TSC
 Output : 75 HP (55 kW)
 Poles : 4
 Frequency : 60 Hz
 Rated voltage : 230/460 V
 Rated current : 174/87.2 A
 L. R. Amperes : 1116/558 A
 LRC : 6.4x(Code G)
 No load current : 66.0/33.0 A
 Rated speed : 1780 rpm
 Slip : 1.11 %
 Rated torque : 221 ft.lb
 Locked rotor torque : 240 %
 Breakdown torque : 260 %
 Insulation class : F
 Service factor : 1.25
 Moment of inertia (J) : 23.3 sq.ft.lb
 Design : B

Locked rotor time : 25s (cold) 14s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Protection degree : IP55
 Cooling method : IC411 - TEFC
 Mounting : F-3
 Rotation¹ : Both (CW and CCW)
 Noise level² : 67.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 957 lb

Output	25%		50%		75%		100%	
Efficiency (%)	94.0	93.6	94.5	93.7	95.0	94.2	95.4	94.2
	93.3	93.0	93.6	93.5	94.2	94.2	94.4	94.6
	94.8	94.7	94.5	94.5	94.1	94.5	93.6	94.1
Power Factor	94.0		94.1		94.5		94.5	
	0.44	0.44	0.68	0.68	0.78	0.78	0.83	0.82
	0.40	0.37	0.64	0.61	0.75	0.73	0.81	0.80
	0.51	0.46	0.75	0.70	0.82	0.80	0.84	0.83
	0.43		0.67		0.78		0.82	

Foundation loads
 Max. traction : 1708 lb
 Max. compression : 2665 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	4.7	4.7	4.7	4.7	4.7	4.7	4.7
	P2 (0,5;1,0)	3.8	3.8	3.8	3.8	3.8	3.8	3.8
	P3 (0,25;1,0)	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	P4 (0,9;0,5)	2.4	2.4	2.4	2.4	2.4	2.4	2.4
	P5 (0,5;0,5)	1.6	1.6	1.6	1.6	1.6	1.6	1.6
	P6 (0,5;0,25)	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	P7 (0,25;0,25)	0.7	0.7	0.7	0.7	0.7	0.7	0.7

	<u>Drive end</u>	<u>Non drive end</u>
Bearing type :	6314 C3	6314 C3
Sealing :	WSeal	WSeal
Lubrication interval :	12000 h	12000 h
Lubricant amount :	27 g	27 g
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/03/2024		Page 1 / 1	Revision