DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W22 NEMA Premium Efficiency Three-Product code: 11165727 Catalog #: 04012ET3H364T-W22 Frame : 364/5T Locked rotor time : 37s (cold) 21s (hot) Output : 40 HP (30 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) : -20°C to +40°C Frequency : 60 Hz Ambient temperature Rated voltage : 575 V : 1000 m.a.s.l. Altitude Rated current : 37.2 A Protection degree : IP55 L. R. Amperes : 238 A Cooling method : IC411 - TEFC LRC : 6.4x(Code G) Mounting : F-1 No load current : 13.2 A Rotation¹ : Both (CW and CCW) Rated speed : 1183 rpm Noise level² : 66.0 dB(A) Starting method Slip : 1.42 % : Direct On Line Rated torque : 178 ft.lb Approx. weight3 : 889 lb Locked rotor torque : 200 % Breakdown torque : 240 % Insulation class : F Service factor : 1.25 Moment of inertia (J) : 21.8 sq.ft.lb Design : B 50% 75% 100% Output Foundation loads Efficiency (%) 93.6 93.6 94.1 Max. traction : 1014 lb Power Factor 0.73 0.82 0.86 Max. compression : 1903 lb Losses at normative operating points (speed;torque), in percentage of rated output power P2 (0,5;1,0) P3 (0,25;1,0) P4 (0,9;0,5) P6 (0,5;0,25) P1 (0,9;1,0) P5 (0,5;0,5) P7 (0,25;0,25) 6.1 5.0 4.4 2.8 1.9 1.1 8.0 Drive end Non drive end Bearing type 6314 C3 6314 C3 WSeal Sealing WSeal Lubrication interval 17000 h 17000 h Lubricant amount 27 g 27 g Lubricant type Mobil Polyrex EM Notes: This revision replaces and cancel the previous one, which These are average values based on tests with sinusoidal must be eliminated. power supply, subject to the tolerances stipulated in NEMA (1) Looking the motor from the shaft end. MG-1. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load. Rev. **Changes Summary** Performed Checked Date Performed by Checked by Page Revision

1/1

28/03/2024

Date