DATA SHEET

Date

29/03/2024



Customer	:							
Product line		: W22 NEMA Premium Efficiency Thre Phase				Product code :	12596017	
	. nacc				Catalog # :		00718ET3V213TC-W22	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor tord Breakdown torqu Insulation class Service factor		: 213/5TC : 7.5 HP (5.5 kW) : 4 : 60 Hz : 200/400 V : 21.1/10.6 A : 150/75.0 A : 7.1x(Code H) : 9.66/4.83 A : 1765 rpm : 1.94 % : 22.3 ft.lb : 220 % : 310 % : F : 1.25				d rotor time rature rise ycle nt temperature estion degree g method ng on¹ evel² g method x. weight³	: 36s (cold) 20s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 58.0 dB(A) : Direct On Line : 171 lb	
Moment of inerti Design	a (J)	: 1.34 : B	4 sq.ft.lb					
Output	25%	50%	75%	100%	Foundation loads			
Efficiency (%)				91.7	Max. traction		: 304 lb	
Power Factor	0.40	0.66	0.76	0.82	Max. cor	npression	: 476 lb	
osses at norma	tive operat	ina points	(speed:tora	ue). in perce	entage of r	ated output power		
P1 (0,9;1,0)					0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25
8.8		7.0 6.5		4.9		3.3	2.4	1.6
Bearing type : Sealing : Lubrication interval : Lubricant amount : Lubricant type :		630	<u>Drive end</u> 6308 ZZ V'Ring - - - Mobil P		Non drive end 6207 ZZ V'Ring - - : EM	<u>1</u>		
Notes:								
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.					These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.		Ch	anges Sum	mary	1	Performed	Checked	Date
Performed by Checked by				-			Page	Revision

1/1