

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 11611340

Catalog # : 00536ET3H184T-W22

Frame : 182/4T
 Output : 5 HP (3.7 kW)
 Poles : 2
 Frequency : 60 Hz
 Rated voltage : 575 V
 Rated current : 4.72 A
 L. R. Amperes : 35.9 A
 LRC : 7.6x(Code J)
 No load current : 1.60 A
 Rated speed : 3500 rpm
 Slip : 2.78 %
 Rated torque : 7.50 ft.lb
 Locked rotor torque : 229 %
 Breakdown torque : 350 %
 Insulation class : F
 Service factor : 1.25
 Moment of inertia (J) : 0.2233 sq.ft.lb
 Design : B

Locked rotor time : 32s (cold) 18s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Protection degree : IP55
 Cooling method : IC411 - TEFC
 Mounting : F-1
 Rotation¹ : Both (CW and CCW)
 Noise level² : 66.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 93.2 lb

Output 25% 50% 75% 100%

Efficiency (%) 0.000 86.5 88.5 88.5
 Power Factor 0.00 0.76 0.85 0.89

Foundation loads

Max. traction : 121 lb
 Max. compression : 214 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
12.2	10.1	9.7	5.9	3.7	2.3	1.5

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6207 ZZ	6206 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	28/03/2024			
		Revision		