

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium Efficiency  
Three-Phase

Product code : 12795530

Catalog # : 00312OT3H213T-S

Frame : 213/5T  
Output : 3 HP (2.2 kW)  
Poles : 6  
Frequency : 60 Hz  
Rated voltage : 575 V  
Rated current : 3.33 A  
L. R. Amperes : 19.6 A  
LRC : 5.9x(Code H)  
No load current : 1.83 A  
Rated speed : 1175 rpm  
Slip : 2.08 %  
Rated torque : 13.4 ft.lb  
Locked rotor torque : 210 %  
Breakdown torque : 260 %  
Insulation class : F  
Service factor : 1.15  
Moment of inertia (J) : 0.8104 sq.ft.lb  
Design : B

Locked rotor time : 70s (cold) 39s (hot)  
Temperature rise : 80 K  
Duty cycle : Cont.(S1)  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Cooling method : IC01 - ODP  
Mounting : F-1  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 55.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 104 lb

Output	25%	50%	75%	100%
Efficiency (%)	85.4	86.5	87.5	88.5
Power Factor	0.33	0.56	0.68	0.75

Foundation loads  
Max. traction : 144 lb  
Max. compression : 248 lb

	Drive end	Non drive end
Bearing type :	6208 ZZ	6206 ZZ
Sealing :	Without Bearing Seal	Without Bearing Seal
Lubrication interval :	-	-
Lubricant amount :	-	-
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
		Revision		