DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Three I hase induction wotor oquirer dage									
Customer	:								
Product line	: W22 Phase	•	ower High	Efficiency T	hree-	Product code	:	12174937	
						Catalog #:		05089EP3HCT364VF	1-W2
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia (: 4 : 60 Hz : 575 V : 47.8 A : 421 A	Code K) Arpm 6		Temp Duty Ambi Altitu Prote Cooli Mour Rotat Noise Starti	ent temperature de ction degree ng method iting		: 14s (cold) 8s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW : 71.0 dB(A) : Direct On Line : 2.2 lb	')
Output	25%	50%	75%	100%	Founda	tion loads			
Efficiency (%)	88.1 82.8	89.5 84.0	91.0 87.5	92.4 88.5	Max. tra	action		: 582 lb	
) ()			0.78 0.52		Max. co	ompression		: 585 lb	
.			Drive			Non drive			

Bearing type : 6314 2RS C3 6314 2RS C3
Sealing : WSeal WSeal
Lubrication interval : - - Lubricant amount : - -

Lubricant type : POLYREA ESTER OIL (WT/ ENS)

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

	П
	ш

Three Phase Induction Motor - Squirrel Cage							
Customer	:						
Voltage: 110-127	7/200-240 V	Space heater informa	ation				
Voltage: 110-127	7200-240 V						
Rev.		Changes Summary	Performed	Checked	Date		
					_		
Performed by							
Checked by				Page	Revision		
Date	28/03/2024			2/2			