

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 NEMA Premium Efficiency Three-Phase

Product code : 14272546

Catalog # : 20018OT3G445T-W40

Frame : 444/5T
 Output : 200 HP (150 kW)
 Poles : 4
 Frequency : 60 Hz
 Rated voltage : 460 V
 Rated current : 234 A
 L. R. Amperes : 1544 A
 LRC : 6.6x(Code G)
 No load current : 86.5 A
 Rated speed : 1783 rpm
 Slip : 0.94 %
 Rated torque : 589 ft.lb
 Locked rotor torque : 210 %
 Breakdown torque : 250 %
 Insulation class : F
 Service factor : 1.15
 Moment of inertia (J) : 46.4 sq.ft.lb
 Design : B

Locked rotor time : 25s (cold) 14s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Protection degree : IP23
 Cooling method : IC01 - ODP
 Mounting : F-1
 Rotation¹ : Both (CW and CCW)
 Noise level² : 78.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 1407 lb

Output	25%	50%	75%	100%				
Efficiency (%)	95.3	95.1	95.4	95.2	95.8	95.6	95.8	95.6
Power Factor	0.46	0.48	0.72	0.74	0.80	0.82	0.84	0.85
	0.44	0.41	0.70	0.67	0.80	0.77	0.84	0.82

Foundation loads
 Max. traction : 3751 lb
 Max. compression : 5158 lb

	Drive end	Non drive end
Bearing type	6319 C3	6314 C3
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	20000 h	20000 h
Lubricant amount	45 g	27 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	29/03/2024			
		Revision		