DATA SHEET



Three Phase Induction Motor - Squirrel Cage					
Customer :					
Product line : W22 Cooling Tower High Efficiency Phase	Three- Product code : Catalog # :	14324021 01526EP3PCT286V-W22			
Frame : 284/6T Output : 3.75 HP (2.8 kW) Poles : 12 Frequency : 60 Hz Rated voltage : 200 V Rated current : 14.8 A L. R. Amperes : 48.9 A LRC : 3.3x(Code E) No load current : 9.20 A Rated speed : 580 rpm Slip : 3.33 % Rated torque : 34.0 ft.lb Locked rotor torque : 130 % Breakdown torque : 180 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 9.16 sq.ft.lb	Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 162s (cold) 90s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-2 : Both (CW and CCW) : 65.0 dB(A) : Direct On Line : 485 lb			
Output 25% 50% 75% 100% Efficiency (%) 78.4 90.9 80.0 91.0 82.5 90.2 84.0 90.3 Power Factor 0.26 0.44 0.44 0.70 0.59 0.81 0.65 0.83		: 631 lb : 1116 lb			
Bearing type : 6311 2RS C3 Sealing : V'Ring Lubrication interval : - Lubricant amount : - Lubricant type : M Notes:	Non drive end 6211 2RS C3 V'Ring - - - obil Polyrex EM				

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024	1		1/2	

DATA SHEET

	П
	ш

Three Phase Induction Motor - Squirrel Cage					
Customer	:				
Voltage: 110-127	7/200-240 V	Space heater informa	ation		
Voltage: 110-127	7200-240 V				
Rev.		Changes Summary	Performed	Checked	Date
					_
Performed by					
Checked by				Page	Revision
Date	28/03/2024			2/2	