DATA SHEET



Three Phase Induction Motor - Squirrel Cage										
Customer		:								
Product line		: W40 NEMA Phase	Premium E	Efficiency Thre	ee- Product code :	14495053				
					Catalog # :	02036OT3H254TC-W40				
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor tord Breakdown torqu Insulation class Service factor Moment of inertia	ue	: 2 : 60 H : 575 : 19.5 : 123 : 6.35 : 353 : 1.94 : 200 : 260 : F : 1.25	HP (15 kW) Hz V 5 A (Code G) 2 A 0 rpm 4 % 3 ft.lb %		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Starting method Approx. weight³	: 19s (cold) 11s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP23 : IC01 - ODP : F-1 : Both (CW and CCW) : Direct On Line : 201 lb				
Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	90.0		91.0	91.0	Max. traction					
Power Factor	0.49	0.72	0.82	0.85	Max. compression					
Bearing type : 6309 Z C3 Sealing : Without Bearing Seal Lubrication interval : 20000 h			9 Z C3 Bearing Seal	Non drive end 6209 Z C3 Without Bearing Seal 20000 h						
Lubricant amount		:		13 g	9 a					

Mobil Polyrex EM

Notes:

Lubricant type

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	29/03/2024			1/1	