DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Three Phase induction Motor - Squirrer Cage						
Customer	:					
Product line	: W22 Cooling Phase	Tower High	Efficiency 1	hree- Product		12173196 02089EP3PCT256V-W22
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia (a	: 4 : 60 F : 200 : 60.0 : 426 : 7.1x : 26.0 : 177 : 1.67 : 59.3 : 270 : 280 : F : 1.15	IP (15 kW) Iz V A A (Code J) A O rpm % ft.lb %		Locked rotor tim Temperature ris Duty cycle Ambient temper Altitude Protection degre Cooling method Mounting Rotation ¹ Noise level ² Starting method Approx. weight ³	ee rature ee I	: 14s (cold) 8s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-2 : Both (CW and CCW) : 64.0 dB(A) : Direct On Line : 2.2 lb
1	25% 50% 86.6 77.3 87.5 78	75%	100%	Foundation loads Max. traction		: 255 lb
, ,	0.38 0.21 0.60 0.3			Max. compression	n	: 257 lb
Bearing type Sealing Lubrication interval Lubricant amount Lubricant type Notes:	: : : :	<u>Drive e</u> 6309 2F V'Ri - -	RS C3 ing		drive end 09 2RS C3 V'Ring - -	

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

	П
	ш

Three Phase Induction Motor - Squirrel Cage						
Customer	:					
Voltage: 110-127	7/200-240 V	Space heater informa	ation			
Voltage: 110-127	7200-240 V					
Rev.		Changes Summary	Performed	Checked	Date	
					_	
Performed by						
Checked by				Page	Revision	
Date	28/03/2024			2/2		