## **DATA SHEET**



Three Phase Induction Motor - Squirrel Cage Customer Product line : W22 High Efficiency Three-Phase Product code: 11356468 Frame : 447/9T Locked rotor time : 28s (cold) 16s (hot) Output : 350 HP (260 kW) Temperature rise : 80 K Poles Duty cycle : 4 : Cont.(S1) Frequency : 60 Hz Ambient temperature : -20°C to +40°C Rated voltage : 460 V Altitude : 1000 m.a.s.l. Rated current : 396 A Protection degree : IP55 : IC411 - TEFC L. R. Amperes : 2534 A Cooling method LRC : 6.4x(Code G) Mounting : F-1 No load current Rotation<sup>1</sup> : Both (CW and CCW) : 98.0 A Rated speed : 1780 rpm Noise level<sup>2</sup> : 75.0 dB(A) Slip : 1.11 % Starting method : Direct On Line Rated torque : 1030 ft.lb Approx. weight3 : 2999 lb Locked rotor torque : 210 % Breakdown torque : 220 % Insulation class : F : 1.15 Service factor Moment of inertia (J) : 118 sq.ft.lb Design : B Output 25% 50% 75% 100% Foundation loads Efficiency (%) 95.3 95.4 95.8 95.8 Max. traction : 4556 lb Power Factor 0.55 0.76 0.84 0.86 : 7555 lb Max. compression Losses at normative operating points (speed;torque), in percentage of rated output power P1 (0,9;1,0) P2 (0,5;1,0) P3 (0,25;1,0) P4 (0,9;0,5) P5 (0,5;0,5) P6 (0,5;0,25) P7 (0,25;0,25) 4.4 3.6 8.0 0.5 3.4 1.9 1.3 Drive end Non drive end Bearing type NU-322 C3 6319 C3 WSeal WSeal Sealing Lubrication interval 4000 h 8000 h Lubricant amount 60 g 45 g Mobil Polyrex EM Lubricant type Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	29/03/2024			1/1	