

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Cooling Tower High Efficiency Three-Phase

Product code : 12174043

Catalog # : 03089EP3PCT326V2F1-W

Frame : 324/6T
Output : 30 HP (22 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 200 V
Rated current : 85.9 A
L. R. Amperes : 670 A
LRC : 7.8x(Code J)
No load current : 29.9 A
Rated speed : 1780 rpm
Slip : 1.11 %
Rated torque : 88.5 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 280 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 9.16 sq.ft.lb

Locked rotor time : 27s (cold) 15s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 69.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 2.2 lb

Output	25%	50%	75%	100%				
Efficiency (%)	89.4	71.3	90.2	74.0	91.7	78.5	92.4	81.5
Power Factor	0.43	0.17	0.65	0.30	0.75	0.40	0.80	0.48

Foundation loads
Max. traction : 457 lb
Max. compression : 459 lb

	Drive end	Non drive end
Bearing type	6312 2RS C3	6212 2RS C3
Sealing	V'Ring	V'Ring
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	28/03/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Space heater information

Voltage: 110-127/200-240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 2		Revision
Checked by					
Date	28/03/2024				