

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 NEMA Premium Efficiency Three-Phase

Product code : 14270939

Catalog # : 06018OT3H364TS-W40

Frame : 364/5TS
 Output : 60 HP (45 kW)
 Poles : 4
 Frequency : 60 Hz
 Rated voltage : 575 V
 Rated current : 55.9 A
 L. R. Amperes : 363 A
 LRC : 6.5x(Code G)
 No load current : 19.8 A
 Rated speed : 1780 rpm
 Slip : 1.11 %
 Rated torque : 177 ft.lb
 Locked rotor torque : 200 %
 Breakdown torque : 240 %
 Insulation class : F
 Service factor : 1.25
 Moment of inertia (J) : 15.6 sq.ft.lb
 Design : B

Locked rotor time : 34s (cold) 19s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : -20°C to +40°C
 Altitude : 1000 m.a.s.l.
 Protection degree : IP23
 Cooling method : IC01 - ODP
 Mounting : F-1
 Rotation¹ : Both (CW and CCW)
 Noise level² : 69.0 dB(A)
 Starting method : Direct On Line
 Approx. weight³ : 746 lb

Output	25%	50%	75%	100%
Efficiency (%)	94.4	94.5	95.0	95.0
Power Factor	0.48	0.73	0.82	0.85

Foundation loads
 Max. traction : 1083 lb
 Max. compression : 1829 lb

	Drive end	Non drive end
Bearing type :	6314 C3	6212 Z C3
Sealing :	Without Bearing Seal	Without Bearing Seal
Lubrication interval :	20000 h	20000 h
Lubricant amount :	27 g	13 g
Lubricant type :	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	28/03/2024			
		Revision		