

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Cooling Tower High Efficiency Three-Phase  
Product code : 12172477  
Catalog # : 00589EP3HCT184V-W22

|                       |                   |                             |                       |
|-----------------------|-------------------|-----------------------------|-----------------------|
| Frame                 | : 182/4T          | Locked rotor time           | : 12s (cold) 7s (hot) |
| Output                | : 5 HP (3.7 kW)   | Temperature rise            | : 80 K                |
| Poles                 | : 4               | Duty cycle                  | : Cont.(S1)           |
| Frequency             | : 60 Hz           | Ambient temperature         | : -20°C to +40°C      |
| Rated voltage         | : 575 V           | Altitude                    | : 1000 m.a.s.l.       |
| Rated current         | : 5.34 A          | Protection degree           | : IP55                |
| L. R. Amperes         | : 39.5 A          | Cooling method              | : IC411 - TEFC        |
| LRC                   | : 7.4x(Code J)    | Mounting                    | : F-2                 |
| No load current       | : 2.96 A          | Rotation <sup>1</sup>       | : Both (CW and CCW)   |
| Rated speed           | : 1750 rpm        | Noise level <sup>2</sup>    | : 58.0 dB(A)          |
| Slip                  | : 2.78 %          | Starting method             | : Direct On Line      |
| Rated torque          | : 15.0 ft.lb      | Approx. weight <sup>3</sup> | : 2.2 lb              |
| Locked rotor torque   | : 200 %           |                             |                       |
| Breakdown torque      | : 300 %           |                             |                       |
| Insulation class      | : F               |                             |                       |
| Service factor        | : 1.15            |                             |                       |
| Moment of inertia (J) | : 0.4461 sq.ft.lb |                             |                       |

|                |      |      |      |      |                  |      |      |      |                  |          |
|----------------|------|------|------|------|------------------|------|------|------|------------------|----------|
| Output         | 25%  | 50%  | 75%  | 100% | Foundation loads |      |      |      |                  |          |
| Efficiency (%) | 83.2 | 64.0 | 84.0 | 66.0 | 86.5             | 72.0 | 87.0 | 74.0 | Max. traction    | : 105 lb |
| Power Factor   | 0.34 | 0.19 | 0.58 | 0.34 | 0.72             | 0.44 | 0.80 | 0.52 | Max. compression | : 107 lb |

|                      |   |                  |                      |
|----------------------|---|------------------|----------------------|
|                      |   | <u>Drive end</u> | <u>Non drive end</u> |
| Bearing type         | : | 6207 2RS         | 6206 2RS             |
| Sealing              | : | V'Ring           | V'Ring               |
| Lubrication interval | : | -                | -                    |
| Lubricant amount     | : | -                | -                    |
| Lubricant type       | : | Mobil Polyrex EM |                      |

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev.         | Changes Summary | Performed                 | Checked | Date |
|--------------|-----------------|---------------------------|---------|------|
|              |                 |                           |         |      |
| Performed by |                 | Page<br>1 / 2<br>Revision |         |      |
| Checked by   |                 |                           |         |      |
| Date         | 28/03/2024      |                           |         |      |

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Space heater information

Voltage: 110-127/200-240 V

|              |                 |  |           |         |          |
|--------------|-----------------|--|-----------|---------|----------|
| Rev.         | Changes Summary |  | Performed | Checked | Date     |
|              |                 |  |           |         |          |
| Performed by |                 |  |           | Page    | Revision |
| Checked by   |                 |  |           |         |          |
| Date         | 28/03/2024      |  |           |         |          |
|              |                 |  |           | 2 / 2   |          |