## **DATA SHEET**



Three Phase Induction Motor - Squirrel Cage								
Customer	:							
Product line	: W22 Cooling To Phase	ower High	Efficiency 1	Three-	Product code Catalog # :	:	14324026 02026EP3QCT324V-W22	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia (J)	: 324/6 : 5 HP ( : 12 : 60 Hz : 460 V : 8.38 A : 40.2 A : 4.8x(C : 5.20 A : 589 rp : 1.83 % : 44.6 ff : 110 % : 250 % : F : 1.15 : 9.79 s	(3.7 kW) Code H) Com 6		Tempe Duty c Ambie Altitud Protec Coolin Mount Rotatic Noise Startin	nt temperature e tion degree g method ing on <sup>1</sup>		: 162s (cold) 90s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-2 : Both (CW and CCW) : 63.0 dB(A) : Direct On Line : 559 lb	
, ,	50% 0.9 86.5 82.0 87.0 25 0.45 0.45 0.72			Max. tra	ion loads ction npression		: 980 lb : 1539 lb	
Bearing type Sealing Lubrication interval Lubricant amount Lubricant type  Notes:	: : : : : : : : : : : : : : : : : : : :	<u>Drive 6</u> 6312 2F V'Ri - -	end RS C3 ng	bil Polyre	Non drive 6212 2R V'Rin - -	S C3		

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

## DATA SHEET

	П
	ш

Three Phase Induction Motor - Squirrel Cage						
Customer	:					
Voltage: 110-127	7/200-240 V	Space heater informa	ation			
Voltage: 110-127	7200-240 V					
Rev.		Changes Summary	Performed	Checked	Date	
					_	
Performed by						
Checked by				Page	Revision	
Date	28/03/2024			2/2		