DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Three Phase induction Motor - Squirter Cage							
Customer	:						
Product line	: W22 Phase		ower High	Efficiency 1	hree-	Product code : Catalog # :	12173001 01089EP3HCT215V-W22
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia (J))	: 213/57 : 10 HP : 4 : 60 Hz : 575 V : 10.4 A : 72.8 A : 7.0x(C : 5.76 A : 1765 r : 1.94 % : 29.8 ft : 210 % : 300 % : F : 1.15	(7.5 kW) ode J) pm		Tempe Duty c Ambie Altitude Protec Coolin Mounti Rotatic Noise Startin	nt temperature e tion degree g method ng on ¹	: 10s (cold) 6s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-2 : Both (CW and CCW) : 61.0 dB(A) : Direct On Line : 2.2 lb
Efficiency (%) 8	6.7 74.4			100% 88.5 81.5	Max. trac		: 168 lb
Power Factor 0.	.36 0.22	0.63 0.42	0.75 0.52	0.82 0.58	Max. cor	npression	: 170 lb
Bearing type Sealing Lubrication interval Lubricant amount Lubricant type		:	<u>Drive 6</u> 6308 V'Ri - -	2RS ing	bil Polyrex	Non drive end 6207 2RS V'Ring - - : EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

	П
	ш

Three Phase Induction Motor - Squirrel Cage						
Customer	:					
Voltage: 110-127	7/200-240 V	Space heater informa	ation			
Voltage: 110-127	7200-240 V					
Rev.		Changes Summary	Performed	Checked	Date	
					_	
Performed by						
Checked by				Page	Revision	
Date	28/03/2024			2/2		