

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Cooling Tower NEMA Premium
Efficiency Three-Phase

Product code : 12024064

Catalog # : 00318ET3HCT182T-W22

Frame	: 182T	Locked rotor time	: 41s (cold) 23s (hot)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 3.13 A	Protection degree	: IP55
L. R. Amperes	: 25.3 A	Cooling method	: IC411 - TEFC
LRC	: 8.1x(Code K)	Mounting	: F-2
No load current	: 1.60 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1760 rpm	Noise level ²	: 56.0 dB(A)
Slip	: 2.22 %	Starting method	: Direct On Line
Rated torque	: 8.95 ft.lb	Approx. weight ³	: 91.2 lb
Locked rotor torque	: 220 %		
Breakdown torque	: 330 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.3401 sq.ft.lb		
Design	: B		

Output 25% 50% 75% 100%

Efficiency (%) 86.4 87.5 88.5 89.5
Power Factor 0.36 0.61 0.71 0.79

Foundation loads

Max. traction : 143 lb
Max. compression : 234 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
11.0	8.9	8.8	6.1	4.0	3.0	2.1

	Drive end	Non drive end
Bearing type	: 6207 2RS	: 6206 2RS
Sealing	: V'Ring	: V'Ring
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			
		Page 1 / 2		Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Space heater information

Voltage: 110-127/200-240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	28/03/2024				