DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer	:						
Product line	: W22 NEI Phase	MA Premium Efficie	ency Thre	e- Product code :		11440653	
	Filase			Catalog # :		03012ET3H326T-W22	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor tor Breakdown torq Insulation class Service factor	: : : : : : :que :: :ue :	: 324/6T : 30 HP (22 kW) : 6 : 60 Hz : 575 V : 29.0 A : 180 A : 6.2x(Code G) : 13.1 A : 1180 rpm : 1.67 % : 134 ft.lb : 220 % : 240 % : F : 1.25		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³		: 37s (cold) 21s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 62.0 dB(A) : Direct On Line : 544 lb	
Moment of inert Design	` '	13.2 sq.ft.lb B					
Output	50%	75% 100%	6	Foundat	on loads		
Efficiency (%) Power Factor		93.0 93.0 0.76 0.82		Max. trac	ction mpression	: 958 lb : 1502 lb	
Losses at norma	tive operating poi	ints (speed;torque)	, in perce	ntage of r	ated output power		
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)		,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25
7.3	6.1	6.0	3	3.6	2.5	1.7	1.2
Bearing type Sealing Lubrication inter Lubricant amou Lubricant type Notes:		6312 C V'Ring 20000 21 g	g h	bil Polyrex	6212 C3 V'Ring 20000 h 13 g		
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.		Changes Summa	ry		Performed	Checked	Date
Dorformeraller							
Performed by Checked by		_				Page	Revision
<u>-</u>	29/02/2024	-				1 / 1	1/2/19/01
Date	28/03/2024					1/1	1