

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12075631

Catalog # : 40018ET3G449TS-W22

Frame	: L447/9TS	Locked rotor time	: 37s (cold) 21s (hot)
Output	: 400 HP (300 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 445 A	Protection degree	: IP55
L. R. Amperes	: 2893 A	Cooling method	: IC411 - TEFC
LRC	: 6.5x(Code G)	Mounting	: F-1
No load current	: 125 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1785 rpm	Noise level ²	: 79.0 dB(A)
Slip	: 0.83 %	Starting method	: Direct On Line
Rated torque	: 1180 ft.lb	Approx. weight ³	: 3135 lb
Locked rotor torque	: 250 %		
Breakdown torque	: 260 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 136 sq.ft.lb		
Design	: B		

Output	25%		50%		75%		100%		Foundation loads	
Efficiency (%)	94.9	95.4	95.4	95.8	95.8	95.8	96.2	96.2	Max. traction	: 8001 lb
	94.9	94.9	95.4	95.4	95.8	95.8	96.2	96.2		
Power Factor	0.55	0.56	0.80	0.81	0.85	0.86	0.88	0.89	Max. compression	: 11136 lb
	0.52	0.48	0.77	0.74	0.84	0.82	0.87	0.86		

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	4.5	4.5	4.5	4.5
	P2 (0,5;1,0)	3.3	3.3	3.3	3.3
	P3 (0,25;1,0)	2.7	2.7	2.7	2.7
	P4 (0,9;0,5)	2.5	2.5	2.5	2.5
	P5 (0,5;0,5)	1.5	1.5	1.5	1.5
	P6 (0,5;0,25)	1.1	1.1	1.1	1.1
	P7 (0,25;0,25)	0.6	0.6	0.6	0.6

		Drive end	Non drive end
Bearing type	:	6314 C3	6314 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	12000 h	12000 h
Lubricant amount	:	27 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			
			Page	Revision
			1 / 1	