

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 13205890

Catalog # : 65018ET3G588/9-W22

Frame : 588/9T
Output : 650 HP (480 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 460 V
Rated current : 734 A
L. R. Amperes : 5432 A
LRC : 7.4x(Code H)
No load current : 235 A
Rated speed : 1790 rpm
Slip : 0.56 %
Rated torque : 1910 ft.lb
Locked rotor torque : 250 %
Breakdown torque : 270 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 301 sq.ft.lb

Locked rotor time : 39s (cold) 22s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 81.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 5217 lb

Output	25%		50%		75%		100%	
Efficiency (%)	95.8	96.1	96.0	96.2	96.5	96.5	96.6	96.5
	95.4	95.4	95.8	95.8	96.2	96.2	96.5	96.5
Power Factor	0.48	0.49	0.71	0.72	0.81	0.81	0.85	0.85
	0.44	0.41	0.68	0.64	0.78	0.76	0.84	0.82

Foundation loads
Max. traction : 10333 lb
Max. compression : 15550 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	4.2	4.2	4.2	4.2
	P2 (0,5;1,0)	3.1	3.1	3.1	3.1
	P3 (0,25;1,0)	2.3	2.3	2.3	2.3
	P4 (0,9;0,5)	2.7	2.7	2.7	2.7
	P5 (0,5;0,5)	1.8	1.8	1.8	1.8
	P6 (0,5;0,25)	1.5	1.5	1.5	1.5
	P7 (0,25;0,25)	0.8	0.8	0.8	0.8

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6322 C3	6319 C3
Sealing	:	Taconite Labyrinth	Taconite Labyrinth
Lubrication interval	:	6000 h	8000 h
Lubricant amount	:	60 g	45 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/03/2024			
			Page	Revision
			1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	29/03/2024				