DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Three i hade inadelion wotor equiter eage											
Customer	:										
Product line	: Ro Pha		Premium E	Efficiency Th	ree- Product code : Catalog # :	14014001 00158ET3J56-S					
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Insulation class Service factor Moment of inertia	ie	: 4 : 60 H : 380 : 2.45 : 20.7 : 1.37 : 175 : 2.78 : 4.50 : 300 : F : 1.15	HP (1.1 kV) Hz /660 V 5/1.41 A 1/11.6 A k(Code K) 1/0.756 A 0 rpm 3 % 0 ft.lb %	V)	Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 37s (cold) 21s (hot) : 70 K : Cont.(S1) : -20°C to +50°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 52.0 dB(A) : Direct On Line : 37.2 lb					
Output	25%	50%	75%	100%	Foundation loads						
Efficiency (%)	0.000	85.5	86.5	86.5	Max. traction	: 114 lb					
Power Factor	0.00	0.59	0.72	0.79	Max. compression	: 151 lb					
Bearing type Sealing Lubrication interval		:	<u>Drive end</u> 6204 ZZ V'Ring 0 h		Non drive end 6202 ZZ Without Bearing Seal 0 h						
Lubricant amount		:		0 g	0 g						

Mobil Polyrex EM

Notes:

Lubricant type

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			1/1	