DATA SHEET



Three Phase	e Indu	ction M	otor - S	Squirrel	Cage		
Customer	:						
Product line	: W2 Phas	•	ower High	Efficiency 7	Γhree-	Product code : Catalog # :	12174826 03089EP3QCT326V2F1- W
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia	•	: 4 : 60 Hz : 460 V : 37.3 A : 291 A	P (22 kW) Code J) A rpm % ti.lb		Temp Duty Ambi Altitud Prote Cooli Moun Rotat Noise Starti	ent temperature de ction degree ng method tting	: 27s (cold) 15s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 69.0 dB(A) : Direct On Line : 596 lb
Output	25%	50%	75%	100%	Founda	ition loads	
Efficiency (%) Power Factor		3 90.2 74.0 7 0.65 0.30			Max. tra	action ompression	: 160 lb : 756 lb
Bearing type Sealing Lubrication interva	al	: : :	<u>Drive</u> 6312 2 V'R	RS C3		Non drive end 6212 2RS C3 V'Ring	

Lubricant amount

Lubricant type Mobil Polyrex EM

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

	П
	ш

Three Pha	se Inductio	n Motor - Squirrel Cage			
Customer	:				
Voltage: 110-127	7/200-240 V	Space heater informa	ation		
Voltage: 110-127	7200-240 V				
Rev.		Changes Summary	Performed	Checked	Date
					_
Performed by					
Checked by				Page	Revision
Date	28/03/2024			2/2	