## **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



Customer Product line : W22 Cooling Tower High Efficiency Three-Product code: 12174046 03089EP3QCT324VF1-Catalog #: W2 Frame : 324T Locked rotor time : 19s (cold) 11s (hot) Output : 30 HP (22 kW) Temperature rise : 80 K Poles : 4 Duty cycle : Cont.(S1) Ambient temperature : -20°C to +40°C Frequency : 60 Hz : 1000 m.a.s.l. Rated voltage : 460 V Altitude Protection degree Rated current : 37.2 A : IP55 : IC411 - TEFC L. R. Amperes : 301 A Cooling method **LRC** : 8.1x(Code J) Mounting : F-1 No load current : 17.0 A Rotation<sup>1</sup> : Both (CW and CCW) Rated speed Noise level<sup>2</sup> : 1780 rpm : 69.0 dB(A) Slip : 1.11 % Starting method : Direct On Line Rated torque : 88.5 ft.lb Approx. weight3 : 532 lb : 270 % Locked rotor torque : 280 % Breakdown torque Insulation class : F Service factor : 1.15 Moment of inertia (J) : 7.85 sq.ft.lb 25% Output 50% 75% 100% Foundation loads Efficiency (%) 89.4 81.0 90.2 82.5 91.0 84.0 91.7 85.5 Max. traction : 24 lb Power Factor 0.39 0.22 0.64 0.38 0.75 0.50 0.81 0.57 : 556 lb Max. compression Drive end Non drive end 6212 2RS C3 Bearing type 6312 2RS C3

Sealing V'Ring V'Ring Lubrication interval

Lubricant amount

Lubricant type Mobil Polyrex EM

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

## DATA SHEET

	П
	ш

Three Phase Induction Motor - Squirrel Cage							
Customer	:						
Voltage: 110-127	7/200-240 V	Space heater informa	ation				
Voltage: 110-127	7200-240 V						
Rev.		Changes Summary	Performed	Checked	Date		
					_		
Performed by							
Checked by				Page	Revision		
Date	28/03/2024			2/2			