## **DATA SHEET**

## Three Phase Induction Motor - Squirrel Cage



Three Phase induction wotor - Squirrer Cage									
Customer	:								
Product line	: W22 Phase	•	ower High	ı Efficiency 1	Γhree-	Product code : Catalog # :		12173030 01089EP3QCT256V2-W2	2
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia	•	: 4 : 60 Hz : 460 V : 12.3 A : 88.2 A	P (7.5 kW)  A A Code H) A rpm % t.lb 6		Temp Duty of Ambie Altitud Prote Coolin Moun Rotat Noise Startin	ent temperature de ction degree ng method ting		: 30s (cold) 17s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-2 : Both (CW and CCW) : 64.0 dB(A) : Direct On Line : 341 lb	
Output  Efficiency (%) Power Factor				100% 0 89.5 81.5 6 0.86 0.65	Max. tra	ition loads action ompression		: 28 lb : 369 lb	
Bearing type Sealing Lubrication interva Lubricant amount Lubricant type	al	: : : : : : : : : : : : : : : : : : : :		RS C3 Ring - -	bil Polyre	Non drive e 6209 2RS V'Ring - - ex EM	3 C3		
Notes:									

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024	1		1/2	

## DATA SHEET

	П
	ш

Three Phase Induction Motor - Squirrel Cage						
Customer	:					
Voltage: 110-127	7/200-240 V	Space heater informa	ation			
Voltage: 110-127	7200-240 V					
Rev.		Changes Summary	Performed	Checked	Date	
					_	
Performed by						
Checked by				Page	Revision	
Date	28/03/2024			2/2		