DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W21 Explosion Proof High Efficiency Three-Product code: 11110803 : 586/7T Locked rotor time Frame : 100s (cold) 56s (hot) Output : 300 HP (220 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) Frequency : 60 Hz Ambient temperature : -20°C to +40°C : 460 V Rated voltage Altitude : 1000 m.a.s.l. Rated current : 329 A Protection degree : IP55 : IC411 - TEFC L. R. Amperes : 2171 A Cooling method **LRC** : 6.6x(Code G) Mounting : F-1 : Both (CW and CCW) No load current : 81.0 A Rotation¹ Rated speed : 1790 rpm Noise level² : 83.0 dB(A) Slip : 0.56 % Starting method : Direct On Line Rated torque : 3851 lb : 880 ft.lb Approx. weight³ Locked rotor torque : 200 % Breakdown torque : 229 % : F Insulation class Service factor : 1.15 Moment of inertia (J) : 163 sq.ft.lb Design : B 25% 50% 100% Output 75% Foundation loads Efficiency (%) 94.9 95.0 95.4 95.4 Max. traction : 2298 lb Power Factor 0.59 0.82 0.87 0.88 Max. compression : 6148 lb Non drive end Drive end Bearing type 6322 C3 6319 C3 Viton Oil Seal Viton Seal Sealing Lubrication interval 5138 h 7038 h Lubricant amount 60 g 45 g Lubricant type Mobil Polyrex EM

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			1/2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



_	
Customer	
Custoffici	

Thermal protection

		•		
ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary Performed		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			2/2	