

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof High Efficiency Three-Phase Product code : 12823585

Frame	: 326TC	Locked rotor time	: 39s (cold) 22s (hot)
Output	: 50 HP (37 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 117/58.7 A	Protection degree	: IP55
L. R. Amperes	: 716/358 A	Cooling method	: IC411 - TEFC
LRC	: 6.1x(Code G)	Mounting	: W-6
No load current	: 42.0/21.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1770 rpm	Noise level ²	: 71.0 dB(A)
Slip	: 1.67 %	Starting method	: Direct On Line
Rated torque	: 148 ft.lb	Approx. weight ³	: 696 lb
Locked rotor torque	: 229 %		
Breakdown torque	: 240 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 9.16 sq.ft.lb		
Design	: B		

Output	25%		50%		75%		100%		Foundation loads	
Efficiency (%)	93.4	91.3	93.0	91.0	93.6	92.4	93.0	91.7	Max. traction	: 1018 lb
	92.0	92.0	91.7	91.7	93.0	93.0	92.4	92.4		
Power Factor	0.47	0.52	0.72	0.76	0.81	0.82	0.85	0.85	Max. compression	: 1714 lb
	0.48	0.45	0.73	0.70	0.80	0.79	0.84	0.84		

					<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:				6312 2RS C3	6212 2RS C3
Sealing	:				Oil Seal	Lip Seal
Lubrication interval	:				-	-
Lubricant amount	:				-	-
Lubricant type	:				Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	27/03/2024			
			Page	Revision
			1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2Revision	
Checked by					
Date	27/03/2024				