DATA SHEET

Three Phase Induction Motor - Squirrel Cage



| | | | | - | | |
|--|------------------------|---|--|--|---|--|
| Customer | : | | | | | |
| Product line | | Explosion ency Three | | MA Premiui | m Product code : Catalog # : | 14356576 35036XT3G449TS |
| Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia Design | e | : 449TS : 350 H : 2 : 60 Hz : 460 V : 379 A : 3297 A : 8.7x(0 : 97.0 A : 3575 I : 0.69 % : 514 ft. : 280 % : 340 % : F : 1.00 : 68.1 s : A | P (260 kW Code J) A rpm 6 .lb | /) | Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³ | : 25s (cold) 14s (hot) : 80 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 84.0 dB(A) : Direct On Line : 3639 lb |
| Output | 25% | 50% | 75% | 100% | Foundation loads | |
| Efficiency (%) Power Factor | 95.2 94.9 0.58 0.60 | 95.0 95.0 0.82 0.83 | 95.8 95.8 0.88 0.88 | 95.8 95.4 3 95.4 95.8 3 0.90 0.90 6 0.89 0.89 | Max. traction Max. compression | : 3536 lb : 7175 lb |
| Bearing type Sealing Lubrication interva Lubricant amount Lubricant type | al | : | Drive 631 Viton 0 360 | end 4 C3 Dil Seal 04 h 7 g | Non drive end 6314 C3 Viton Seal 3604 h 27 g bil Polyrex EM | |
| Notes: | | | | | | |

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev. | | Changes Summary | Performed | Checked | Date |
|--------------|------------|-----------------|-----------|---------|----------|
| | | | | | |
| Performed by | | | | | |
| Checked by | | | | Page | Revision |
| Date | 28/03/2024 | | | 1/2 | |

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



| _ | |
|------------|--|
| Customer | |
| Custoffici | |

Thermal protection

| l | | • | | |
|----|-------------|----------------------|-----------|---------------------|
| ID | Application | Туре | Quantity | Sensing Temperature |
| 1 | Winding | Thermostat - 2 wires | 1 x Phase | 155 °C |

| Rev. | Changes Summary | | Performed | Checked | Date |
|--------------|-----------------|--|-----------|---------|----------|
| | | | | | |
| Performed by | | | | | |
| Checked by | | | | Page | Revision |
| Date | 28/03/2024 | | | 2/2 | |