

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 12408378

Catalog # : 15012XT3G504

Frame : 504/5T
Output : 150 HP (110 kW)
Poles : 6
Frequency : 60 Hz
Rated voltage : 460 V
Rated current : 174 A
L. R. Amperes : 1305 A
LRC : 7.5x(Code H)
No load current : 66.0 A
Rated speed : 1190 rpm
Slip : 0.83 %
Rated torque : 662 ft.lb
Locked rotor torque : 260 %
Breakdown torque : 260 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 134 sq.ft.lb
Design : B

Locked rotor time : 75s (cold) 42s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 73.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 2715 lb

Output	25%	50%	75%	100%				
Efficiency (%)	94.9	94.4	95.0	94.5	95.8	95.0	95.8	95.0
Power Factor	0.44	0.44	0.68	0.68	0.78	0.78	0.83	0.83
	0.41	0.38	0.65	0.62	0.76	0.74	0.82	0.80

Foundation loads
Max. traction : 3574 lb
Max. compression : 6289 lb

	Drive end	Non drive end
Bearing type	6319 C3	6316 C3
Sealing	Viton Oil Seal	Viton Seal
Lubrication interval	11094 h	12823 h
Lubricant amount	45 g	34 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2		
Checked by				
Date	28/03/2024			
		Revision		

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2Revision	
Checked by					
Date	28/03/2024				