DATA SHEET

Three Phase Induction Motor - Squirrel Cage



				•	3		
Customer		:					
Product line		: W21 Explosion		EMA Premiui	m Product code : Catalog # :	14407172 03018XT3H286T	
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torq Breakdown torqu Insulation class Service factor Moment of inertia	е	: 4 : 60 F : 575 : 28.1 : 171 : 6.1x : 9.84 : 1770 : 1.67 : 89.0 : 240 : F : 1.15	IP (22 kW) Iz V A A (Code G) A O rpm W If lb		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 30s (cold) 17s (hot) : 105 K : Cont.(S1) : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : F-1 : Both (CW and CCW) : 68.0 dB(A) : Direct On Line : 496 lb	
Output	25%	50%	75%	100%	Foundation loads		
Efficiency (%)	92.3	93.0	93.0	93.6	Max. traction	: 684 lb	
Power Factor	0.46	0.70	0.80	0.84	Max. compression	: 1178 lb	
Bearing type Sealing Lubrication interv Lubricant amount		: : : :	63 Oi 20	<u>e end</u> 11 C3 I Seal 1000 h 18 g	Non drive end 6211 C3 Lip Seal 20000 h 11 g		
Lubricant type		:		Mo	bil Polvrex EM		

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



_	
Customer	
Custoffici	

Thermal protection

1		•		
ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			2/2	