DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Product line : Fan and Exhaust Single-Phase Start Product code: 11748502 Catalog #: 00182OS1DEC56 Frame : E56X180 Locked rotor time : 10s (cold) 6s (hot) Output : 0.75 kW (1 HP) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) : -20°C to +40°C Frequency : 60 Hz Ambient temperature Rated voltage : 240 V : 1000 m.a.s.l. Altitude Rated current : 6.45 A Protection degree : IP21 L. R. Amperes : 31.0 A Cooling method : IC01 - ODP LRC : 4.8x(Code J) Mounting : F-1 No load current : 4.89 A Rotation¹ : CW Rated speed : 1725 rpm Noise level² : 46.0 dB(A) Starting method : Direct On Line Slip : 4.17 % Rated torque : 3.06 ft.lb Approx. weight³ : 30.9 lb Locked rotor torque : 125 % Breakdown torque : 240 % Insulation class : B Service factor : 1.00 Moment of inertia (J) : 0.1092 sq.ft.lb 25% 75% 100% 50% Foundation loads Output Efficiency (%) 0.000 60.1 65.7 66.7 Max. traction Power Factor 0.00 0.50 0.63 0.72 Max. compression Drive end Non drive end Bearing type 6203 ZZ 6201 ZZ Without Bearing Seal Without Bearing Seal Sealing Lubrication interval 0 h 0 h Lubricant amount 0 g 0 g Lubricant type Mobil Polyrex EM

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer		

Thermal protection

ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	130 °C

Rev.		Changes Summary		Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			2/2	