DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W21 Explosion Proof NEMA Premium Product code: 14407175 Efficiency Three-Phase Catalog #: 05018XT3H326T Frame : 326T Locked rotor time : 28s (cold) 16s (hot) Output : 50 HP (37 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) : -20°C to +40°C Frequency : 60 Hz Ambient temperature Rated voltage : 575 V : 1000 m.a.s.l. Altitude Rated current : 48.6 A Protection degree : IP55 L. R. Amperes : 354 A Cooling method : IC411 - TEFC : 7.3x(Code H) LRC Mounting : F-1 No load current : 20.0 A Rotation¹ : Both (CW and CCW) Rated speed : 1775 rpm Noise level² : 71.0 dB(A) Starting method Slip : 1.39 % : Direct On Line Rated torque : 148 ft.lb Approx. weight³ : 685 lb Locked rotor torque : 260 % Breakdown torque : 280 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 9.16 sq.ft.lb Design : B 25% 50% 75% 100% Output Foundation loads 94.5 Efficiency (%) 93.4 93.6 94.5 Max. traction : 1248 lb Power Factor 0.41 0.76 0.81 0.65 Max. compression : 1931 lb Non drive end Drive end Bearing type 6312 C3 6212 C3 Oil Seal Sealing Lip Seal Lubrication interval 20000 h 20000 h Lubricant amount 21 g 13 g Lubricant type Mobil Polyrex EM

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			1/2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



_	
Customer	
Custoffici	

Thermal protection

l		•		
ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/03/2024			2/2	