

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium Efficiency
Three-Phase

Product code : 12759403

Catalog # : 02036ET3E256T-SG

Frame : 254/6T
Output : 20 HP (15 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 45.4/22.7 A
L. R. Amperes : 300/150 A
LRC : 6.6x(Code G)
No load current : 13.8/6.88 A
Rated speed : 3515 rpm
Slip : 2.36 %
Rated torque : 29.9 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 290 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 1.22 sq.ft.lb
Design : B

Locked rotor time : 21s (cold) 12s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 75.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 219 lb

Output	25%	50%	75%	100%
Efficiency (%)	89.7	90.0	91.0	91.0
Power Factor	0.55	0.81	0.88	0.91

Foundation loads
Max. traction : 306 lb
Max. compression : 525 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6309 Z C3	6208 Z C3
Sealing	:	V'Ring	Without Bearing Seal
Lubrication interval	:	15797 h	20000 h
Lubricant amount	:	13 g	8 g
Lubricant type	:	Mobil Polyrex EM	

Notes:
USABLE @208V 50.2A SF 1.00 SFA 50.2A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	27/03/2024			
		Revision		