

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 14406980

Catalog # : 00712XT3E254T

Frame : 254T
Output : 7.5 HP (5.5 kW)
Poles : 6
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 19.5/9.73 A
L. R. Amperes : 136/68.1 A
LRC : 7.0x(Code J)
No load current : 10.4/5.20 A
Rated speed : 1175 rpm
Slip : 2.08 %
Rated torque : 33.5 ft.lb
Locked rotor torque : 270 %
Breakdown torque : 320 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 3.32 sq.ft.lb
Design : B

Locked rotor time : 45s (cold) 25s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 59.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 327 lb

Output	25%		50%		75%		100%	
Efficiency (%)	87.5	90.1	88.5	89.5	90.2	89.5	91.0	88.5
	89.8	89.8	89.5	89.5	90.2	90.2	89.5	89.5
Power Factor	0.34	0.40	0.58	0.65	0.71	0.77	0.78	0.82
	0.37	0.34	0.62	0.59	0.74	0.72	0.81	0.79

Foundation loads
Max. traction : 386 lb
Max. compression : 710 lb

	Drive end	Non drive end
Bearing type	: 6309 C3	: 6209 C3
Sealing	: Oil Seal	: Lip Seal
Lubrication interval	: 20000 h	: 20000 h
Lubricant amount	: 13 g	: 9 g
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	28/03/2024			

Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date	28/03/2024				