DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W22 NEMA Premium Efficiency Three-Product code: 13500620 Catalog #: 30009ET3GKD586/7-W22 Frame : 586/7T Locked rotor time : 72s (cold) 40s (hot) Output : 300 HP (220 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) : -20°C to +40°C Frequency : 60 Hz Ambient temperature Rated voltage : 460 V : 1000 m.a.s.l. Altitude Rated current : 356 A Protection degree : IP55 : 2670 A L. R. Amperes Cooling method : IC411 - TEFC : 7.5x(Code H) LRC Mounting : F-1 No load current : 150 A Rotation¹ : Both (CW and CCW) Rated speed : 895 rpm Noise level² : 75.0 dB(A) Starting method Slip : 0.56 % : Direct On Line Rated torque : 1760 ft.lb Approx. weight³ : 4518 lb Locked rotor torque : 200 % Breakdown torque : 229 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 451 sq.ft.lb 25% 50% 75% 100% Foundation loads Output Efficiency (%) 0.000 95.4 95.8 95.8 Max. traction : 6188 lb Power Factor : 10706 lb 0.00 0.66 0.77 0.81 Max. compression Drive end Non drive end NU-322 C3 Bearing type 6319 C3 Taconite Labyrinth Taconite Labyrinth Sealing Lubrication interval 13000 h 17000 h Lubricant amount 60 g 45 g

Mobil Polyrex EM

Notes:

Lubricant type

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			1/2	

DATA SHEET

	П
Ш	Ш

Three Pha	se Induction	<u> </u>			
Customer	:				
Voltage: 200 - 24	10 V	Space heater infor	mation		
Rev.		Changes Summary	Performed	Checked	Date
Dorformadhi		I			
Performed by Checked by				Page	Revision

2/2

27/03/2024

Date